



N.Z.P.O.	AMENDMENT PARTICULARS	DATE	APP	REF: GEC DRG 5.6552	SIZE	M	SOV	H
	RETRACED & METRICATED (157663)	5A	14.7.78	RED				
	NOTE 8 & METRIC WIRE SIZES ADD NZ NOTE DEL(39935)	5	15.2.72	B-9-H				
DRAWN	CHECKED	WIRING	CIRCUIT	200 LINE FINAL SELECTOR ORD.				
1/MC	5/10	5/10		POSITIVE BATTERY METERS				
				2000 TYPE				
				<input type="checkbox"/> SLOW RELEASE <input checked="" type="checkbox"/> SLOW OPERATE				
				GBW 10772				

- NOTES:-**
- FUSE:-R.C.1.5A PER CIRCUIT (R.C.3.0A) POS BATT-0.5A PER 10 CCTS
 - CONTACTS II OF LEVEL I TO BE MULTIPLIED AND WIRED TO MISC. STRIP CONN.
 - Ø FOR WIRING SEE G.B.W.10680 OR EQUIV.
 - WHEN FULL AVAILABILITY FROM GROUP SELECTORS IS SPECIFIED INCOMING LEADS ARE CABLED DIRECT FROM BANK MULT STRIP CONN AND NOT VIA T.D.F. IN SUCH CASES THE FOLLOWING STRAPS MUST BE ADDED ON SITE a) IN ALL CASES STRAP U11 TO U7 b) WHEN NO SELECTOR IS EQUIPPED STRAP U9 TO U7
 - ALL WIRING TO BE 0.5mm UNLESS OTHERWISE SPECIFIED
 - WHEN A CENTRALISED I.D.F. IS SPECIFIED THE - & P TERM'LS ON THE BANK MULT STRIP CONN. ARE CABLED TO IDF MULT.
 - ON EARLY EQUIPMENT, NEG. & POS. BATT WIRING WAS BK OR W AND R-B RESPECTIVELY.
 - WHEN LOCAL METERING IS NOT REQUIRED INSERT STRAP AS SHOWN THUS -|-

BATT.V. :- U12-WS6-HE-R4b-R5b-R6b-R3b-Ae-VMc-RMc-RB1b-RBb
 EARTH R:- U11-D21-D4-CD22-CD24-CD1-H3-Ab-B25-B6-DAa-DA3-DB3
 -MR1a-RB1d-R9a-TJ7-TJ9
 POS. BATT Y :- U20-R1b

BATT.V. 0.9mm.FUSE — (6B) — U12
 ETH.R.0.9mm. ETH. — (6A) — U11
 BAR