


FROM SELECTOR LEVELS.  
NOTE 5

- NOTES**
1. FUSING 1.5A PER RELAY SET, 2 CIRCUITS.
  2. U POINTS U9 AND U11, U17 AND U19 SHOULD MAKE CONTACT WHEN RELAY SET IS REMOVED.
  3. LEADS K1 AND K2 ONLY REQUIRED WHEN POSITIONS ARE KEY-ENDED.
  4. Ø FOR WIRING SEE GBW.10640 OR EQUIV.
  5. WHEN FULL AVAILABILITY FROM SELECTOR LEVELS IS SPECIFIED, INCOMING LEADS ARE CABLED DIRECT FROM BANK MULT STRIP CONN, AND NOT VIA T.D.F.

ETH. ETH. BAR. 20 SWG R (3A) U11-U17  
 BATT. FUSE 20 SWG BK (3B) U12  
 ETH. (R) U11-JRa-B1-B4-BG-SS1-B1-B4-BG-JRa-L21-Lb-Sa-S1-SS1-Sd-S1-L21-Lb-T1-T1  
 BATT. (W) U12-YA2-YB2-Bc-SSe-Bc-Le-SSe-Le-YA2-YB2



ALTERNATIVE CONNECTIONS FOR KEY-ENDED TERMINATION.

TOLL POSITION (EXPLANATORY ONLY)

		SLOW RELEASE		SLOW OPERATE	
DIRECTORY SERVICE RELAY SET SLEEVE CONTROL MANUAL BOARD 2000 TYPE EQUIPMENT					
AMENDMENT PARTICULARS		(7913)	15-7-53	DW	
ISSUE DATE			APP.		
				SIZE M / 50V / S	
12030 G.P.					
DRAWN		CHECKED		WIRING	