



- NOTES:-
- FUSING 1.5A PER CIRCUIT
 - SHELF JACK U POINTS 9 AND 11, 17 AND 19 MAKE CONTACT WHEN RELAY SET IS REMOVED.
 - Ø FOR WIRING SEE GBW.10640 OR EQUIV.
 - (a) WHEN RELAY SET IS AVAILABLE TO REGULAR AND C.C.B. SELECTORS STRAP U15 TO U9 THUS -1-1-
 (b) WHEN DIRECT CABLING FROM GROUP SELECTOR LEVEL IS USED AND THE RELAY SET IS AVAILABLE TO REGULAR SELECTORS ONLY STRAP U15 TO U11 THUS -2-2-
 (c) WHEN DIRECT CABLING FROM GROUP SELECTOR LEVEL IS USED AND THE RELAY SET IS NOT EQUIPPED, STRAP U9 TO U11 TO U15 THUS -1-1- AND -2-2-

BATT. BK. 0.9mm FUSE 6B2 U12
 ETH. R. 0.9mm ETH. BAR 6A2 U11
 U19

BATT. W. U12-CBe-Dee-HJe-SKe-Be-CDe-CCe-RB1b-R1b-R2b-R3b.
 ETH. R. U11-TR1/10-TR1/E-CB1-DDa-HJ2B-HJ1-MHa-MH1-SK23-SK1-B21-B1-CD1-CC23-A2-RB1d-TJ1-TJ9

PROOF

REF:- TR 1039.17.15.		50V W	<input type="checkbox"/> SLOW RELEASE	<input checked="" type="checkbox"/> SLOW OPERATE						
BOTHWAY JUNCTION R/S A.M.X.-TOLL DEMAND (FOR ORD. & COINBOX SUBS) 2000 TYPE										
DEL	CKD	APD	ORDER	DATE	ISS	CHANGE	N Z P O			
DTM	CHW	65499	17030	17-8-55	3	REFS TO T.C.F. ADDED, REDRAWN RETRACED FROM COY. 195.6	ENGINEER-IN-CHIEF, WELLINGTON			
							CO	ORIGIN: T-EQPT		
							10	DRAWN: T.C.F. TRACED:		
							A2 GBW.12280			

