



- NOTES
1. FUSE:- FIG. 2. 1.5A PER CIRCUIT
FIG. 4. 1.5A PER 10 BUSY LAMP RESISTORS
 2. ALL WIRING TO BE 25 SWG. UNLESS OTHERWISE SPECIFIED.
 3. FOR WIRING OF LEADS SHOWN Ø SEE G.B.W. 10690 OR EQUIV.
 4. WHEN FIGS 1&5 ARE EQUIPPED ON THE SAME POSITION, TERMINAL LA (FIG.1) IS NOT REQUIRED.
 5. R1 WAS 1.2K ON EARLIER EQUIPMENTS.

N.Z. NOTE A. AT WANGANUI RELAY'S COIL IS 30 OHMS.

| FIGS. 3 & 6 MODIFIED. | | | | 12A | 4.6.65 | 8. |
|---|--|-------|---------|--------|-----------------|--------------|
| SERVICE DESK STRIP CONN. DESG & REFS. TO FIG. 4. REVISED IN FIG. 3. | | | | 11A | | |
| FIG. 6. KA3 DELETED. KA2 SPRING NUMBERING AMENDED | | | | 10A | | |
| KA3 (FIG. 6) WAS NOT SHOWN. | | | | 9A | | |
| FIG. 6. ADDED, FIGS. 3&4 MODIFIED | | | | 8A | | |
| AMENDMENT PARTICULARS | | ISSUE | DATE | APPD. | REF:- G53-13-20 | SIZE M 50V H |
| N.Z. P.O. | | DRAWN | CHECKED | WIRING | CIRCUIT | GBW 12900 |