



- NOTES :-**
1. FUSING - 1.0A PER CCT.
 2. Ø FOR WIRING SEE GBW 13730 OR EQUIV.
 3. UNLESS OTHERWISE INDICATED ALL TERMINALS ARE ON STRIP CONNEXION AT REAR AND ARE DESIGNATED SC IN WIRING RUNS.
 4. ALL WIRE TO BE 25 S.W.G. UNLESS OTHERWISE SPECIFIED.
 5. DELETED.
 6. AT EXCHANGES WHICH PROVIDE FOR ONLY 2 PARTY LINES & DIAG. GBW 13760 IS NOT FITTED USE CONNECTION SHOWN - 1-1-1 & OMIT - 2-2-2 - OTHERWISE USE - 2-2-2 & OMIT - 1-1-1

N.Z. NOTE A :-
 WHEN USED WITH REMOTE 'M' UNITS PROVIDE - 3-3-3 & OMIT - 4-4-4 AT OTHER INSTALLATIONS PROVIDE - 4-4-4 & OMIT - 3-3-3

FROM RINGING CODES CCT
 GBW 13760 OR EQUIV.
 NOTE 6

SLOW RELEASE		SLOW OPERATION	
U.A.X. N.Z.13			
REVERTIVE CALL RELAY SET FOR 2 PARTY & 5 PARTY LINES			
RETRACED (68204)	9A	13.5.76	63W
NZ NOTE ADDED (86829)	9A	5.6.89	GE
NU RELAY & ASSOC'D WIRING REVISED (47279)	9	11.2.65	DIB
AMENDMENT PARTICULARS	ISSUE DATE	APP'D	
NZPO			
GBW 13770		SIZE: A1	50V C