

I.J.F. (MULT),
T.D.F. O/G
OR T.C.F.

205.W.G

BATT BK FUSE 2B1 12 V
ETH R ETH BAR 2B2 11 V
BATT W U12-ASb-A5e-Ae-Ee-He-RSe-BAe-C5e-Be-B5b-B5e-R2b
ETH R U11-A53-Ab-E1-E3-BA26-C5Ej1-CS1/W-CS2/W-R3a-B23-B1-B524-TJ1.

- 1 FUSING 1-5A PER CIRCUIT.
- 2 PROVIDES (1) PARTY LINE REVERTIVE RINGING AND (2) FAULTSMAN'S RING BACK WHEN DIGITS 90 AND 92 RESPECTIVELY ARE DIALLED INTO THE RELAY SET (N Z NUMBERING) USING 2 PARTY LINE METER DISCRIMINATING CIRCUIT GBW 12080 OR SHARED SERVICE SEPARATE METERING SUBSCRIBERS LINE CIRCUIT GBW 12070 OR EQUIV. EXCEPT WHERE NOTE 14 OF G.B.W. 12070 OR EQUIV APPLIES
3. WHEN EXCHANGE IS EQUIPPED WITH A SINGLE LINE CIRCUIT TWO PARTY LINE GROUPS WITHOUT METER DISCRIMINATION OR NOTE 14 OF GBW 12070 OR EQUIV. APPLIES, DISCONNECT STRAP SHOWN AND ADD STRAPS SHOWN X X RINGING CODES FOR FAULTSMEN ARE THEN AS FOLLOWS -'92' INDIVIDUAL LINES -'93'X PARTY LINES -'94'Y PARTY LINES
- 4 SELF JACK U POINTS 9&11 MAKE CONTACT WHEN RELAY SET IS REMOVED.
5. ON UNISELECTOR BANK STRAPS ON ADJACENT CONTACTS TO BE 25 SWG B.T.C. STRAPS ON NON-ADJACENT CONTACTS ARE TO BE 25 SW.G. OR 23 SW.G. B.T.C WITH SLEEVING. ALL OTHER WIRING OF PLUG IN UNIT TO BE 25 SW.G.
- 6 Ø FOR WIRING SEE G.B.W. 10640 OR EQUIV.
- 7 ON SOME EARLY EQUIPMENT 6 MIN ALARM DELAY IS USED.

FROM SELECTOR LEVELS

TRAFFIC RECORDER WHEN SPECIFIED

NZPO	
PREPARED FROM GBW 13830 MOD A OR 13830 MOD B	
AMENDMENT PARTICULARS	
ISS DATE	
APP	

GBW 13830 MOD A

REVERTIVE RINGING RELAY SET FOR SHARED SERVICE SUBSCRIBERS AND FAULTSMEN

F.U. ON TROMBONE SA-X PARENT EXCHANGES

RELEASE SLOW OPERAT

OPERAT SLOW RELEASE

