



FROM GROUP SELR LEVEL VIA IDF LOCAL

TO INCOMING JUNCTION GROUP GBW 13990  
OR EQUIV. OR TO  
GBW 13960 OR EQUIV. GROUP SELECTOR VIA IDF LOCAL

TO JUNCT. VIA IDF MULT.

N.Z. NOTE  
A. WHEN ROUTE RESTRICTION FACILITIES NOT REQD. REMOVE -2-2-

- NOTE
1. FUSE - 10A PER CIRCUIT
  2. X FOR WIRING SEE BBW 13750 OR EQUIV.
  3. WHEN REPEAT METERING IS NOT REQD. OMIT STRAP BETWEEN SC34 & 25
  4. ALL WIRING TO BE LEAD SWG UNLESS OTHERWISE SPECIFIED
  5. UNLESS OTHERWISE SPECIFIED ALL TERMINALS ARE ON STRIP CONN. AT REAR AND ARE DESIGNATED SCIN WIRING RUNS
  6. RELAY OC IS DIFFERENTIALLY CONNECTED
  7. WHEN JUNCTION RESISTANCE EXCEEDS 200 OHMS STRAP TERMINALS 32 & 42

SLOW RELEASE     SLOW OPERATE

UAX NZ13 OUTGOING JUNCTION TO NON-DEPENDENT AUTO EXCH WITH 1/C JUNCT BARRING FACILITY

CONNECTION BETWEEN DS4 & DS22 DELETED (2433)	3	3047	BSH
MOD. OF ISSUE SA FTH USE AS GBW 1385 (9/24/49)	A	3-7	PLA
AMENDMENT PARTICULARS	ISSUE DATE	APPD	
			SIZE M 50Y H
N.Z.P.O.	DRAWN	CHECKED	WIRING
			CIRCUIT

GBW 13950 MOD.A