



NOTE
ON EXTENSIONS
BARRED DIRECT
ACCESS DISCONNECT
STRAP BD-FT.

EXPLANATORY
PART OF
EXTENSION LINE AND
LINE FINDER CIRCUIT.
GBW 14090 OR EQUIV.

FIG. 1
SELECTOR

FIG. 2
T.D.F. OR
GRADING
SHELF
NOTE 7.

- NOTES
1. FUSE 11-5A PER SELECTOR.
 2. Ø FOR WIRING SEE GBW 14240 OR EQUIV.
 3. JACK POINTS U17-U19 MAKE WHEN SELECTOR IS REMOVED.
 4. NP SPRINGS MAKE ON N.Z. LEVEL 1.
 5. OUTLET 10 ON N.Z. LEVEL 2 IS WIRED VIA THE ROUTINE TEST JACK AND CABLED FROM THE SHELF MISC. STRIP CONN. AS SHOWN ON COMMON SERVICES DIAGRAM GBW 14240 OR EQUIV.
 6. ALL WIRING BEARING A COLOUR CODE TO BE 25 SWG UNLESS OTHERWISE SHOWN. SWITCHPLATE WIRING TO BE 25 SWG.
 7. ON LEVELS WITH FULL AVAILABILITY, OR WHERE A TWO-GROUP GRADING IS PRODUCED BY THE SHELF-TO-SHELF TIE CABLES, OMIT CONNECTIONS SHOWN X AND USE CONNECTIONS SHOWN O.
 8. 'L' LEAD IS NOT REQUIRED IN CABLING TO EXCH. LINE CTS OR NIGHT SERVICE ACCESS CTS.

BATT: BK (20 SWG): FUSE (1B) U12
ETH: R (20 SWG): ETH BAR (1A) U11
BATT: W: U12-ST2-Ae-VMe-RMe-R5b-R6b-U10
ETH: R: U11-ST3-B25-Ba-B6-Ab-A1-N21-S1-NP21-R3a-R4a

N	NR	TJ	NP	S
4	1	14	1	5

AMENDMENT	PARTICULARS	ISSUE DATE	APP

SLOW RELEASE SLOW OPERATE
FIRST GROUP SELECTOR
 50/1200 LINE P.A.B.X.
GBW 14090
 N.Z. PO DRN CHK. WIRING CUBI.