



NOTE  
ON EXTENSIONS  
BARRED DIRECT  
ACCESS  
DISCONNECT  
STRAP BD-FT

EXPLANATORY  
PART OF EXTENSION  
LINE & LINE FINDER  
CIRCUIT.  
GBW 14080 OR EQUIV.

FIG. 2.  
T.D.F. OR  
GRADING  
SHELF  
NOTE 7

FIG. 1.  
SELECTOR.

N	NR	TJ	NP	S
4	1	14	1	5

- NOTES:-
- 1 FUSE 1.5A PER SELECTOR.
  - 2 Ø FOR WIRING SEE GBW 14240 OR EQUIV.
  - 3 JACK POINTS U17-U19 MAKE WHEN SELECTOR IS REMOVED.
  - 4 NP SPRINGS MAKE ON NZ LEVEL 1.
  - 5 OUTLET 10 ON NZ LEVEL 2 IS WIRED VIA THE ROUTINE TEST JACK & CABLED FROM THE SHELF MISC. STRIP CONN. AS SHOWN ON COMMON SERVICES DIAGRAM GBW 14240 OR EQUIV.
  - 6 ALL WIRING BEARING A COLOUR CODE TO BE 25SWG UNLESS OTHERWISE SHOWN. SWITCHPLATE WIRING TO BE 25SWG.
  - 7 ON LEVELS WITH FULL AVAILABILITY, OR WHERE A TWO GROUP GRADING IS PRODUCED BY THE SHELF - TO SHELF TIE CABLES OMIT CONNS. SHOWN 'x' & USE CONNS. SHOWN 'o'.
  - 8 'L' LEAD IS NOT REQUIRED IN CABLING TO EXCH. LINE CCTS. OR NIGHT SERVICE ACCESS CCTS.

- BATT BK (22SWG) FUSE (1B) U12
- ETH. R. (22SWG) ETH BAR (1A) U11
- BATT W. U12-ST2-AE-VM2-RM2-R5b-R6d-U10
- ETH. R. U11-ST3-B25-2d-BG-Ab-7-A1-N2-S1-NP21-R3a-R4a

				<b>FIRST GROUP SELECTOR</b>	
				50/1200 LINE P.A.B.X.	
		(69398)			
AMENDMENT PARTICULARS		ISSUE DATE		APP	
NZPO		DRN	CHK	WIRING	CIRCUIT
		M.H.		RED.	
<b>GBW 14091</b>					