

NOTES:-

1. FUSING: 1.5A PER RELAY SET.
2. DELETED.
3. Ø FOR WIRING SEE GBW 10640 OR EQUIVALENT.
4. JACK POINTS 9 & 11 AND 59 & 61 TO MAKE CONTACT WHEN THE RELAY SET IS REMOVED.
5. ALL WIRING TO BE 25 SWG UNLESS OTHERWISE SPECIFIED.
6. CUT STRAP —— X —— WHEN THE JUNCTION RESISTANCE IS LESS THAN 200Ω.
7. THE COILS OF RELAY TO ARE CONNECTED DIFFERENTIALLY.
8. STRAP —— I —— WHEN REPEAT METERING CCT IS NOT EQUIPPED.
9. DELETED.

NZPO NOTES

A. THIS CIRCUIT USES THE INCOMING & TOLL ENTRY OF GBW 14760 FOR RURAL PARTY & COIN BOX SUBSCRIBERS SO THAT A ROUTE BARRING SIGNAL MAY BE GIVEN TO THE ASSOCIATED MUTI-FEE RELAY SET.

BATT. W. U12-TCe-CBe-CCe-RB1b-DDe-AAe-BAe-R4b-R5b-R6b-R3b

ETH. R. U11-TR1/9-TR1/8-TC6 —— CDa-CD4-JG21-JGa-JG1-DAa-DD23-BB21-BBa-BB1 —— B21-AA22-AA3-A2-BA26-BA5-BA8-RBa-RB1d-TJ1-TJ15

BATT. 22 SWG. BK. FUSE —— (4B) —— U12

ETH. 22 SWG. R. 8TH BAR —— (4A) —— U11-U61

POS. BATT. R.B. U4-R1b

GBW 14760 MOD A