



TO POSITION C.T.
GBW 15201 FIG. 1A
OR EQUIV.

TO CORD CIRCUIT
LAMP & KEYS
GBW 15201 FIG. 2
OR EQUIV.

- NOTES:-
1. FUSE 1.5A PER BASE (3 CCTS)
 2. RELAY D IS DIFFERENTIALLY CONNECTED.
 3. ALL WIRING TO BE 0.5mm. UNLESS OTHERWISE SPECIFIED.
 4. ON SOME EARLY EQUIPMENT BATT. WIRING COLOURS BK.

BATT. V. (0.7mm) FUSE **1B2** U12-U28-U62
EARTH R. (0.7mm) ETH. BAR **1A2** U11-U27-U61

BATT. V. U12-IDe-IDRe-ISRe-ISkE-ISkE
U28-2De-2DR2-2SR2-2SR2-2SR2-2SR2
U62-3SR2-3SR2-3SR2-3SR2-3SR2
EARTH R. U11-1AS21-IDb-IDR21-IDR21-IDR21-ILA4-
1SR1-1SR3-1SR5-1R1a.
U27-2AS21-2Db-2DR21-2DR21-2LC24-
2LA4-2SR1-2SR3-2SR5-2R1a.
U61-3LC24-3LA4-3SR1-3SR3-3SR5-
3AS21-3Db-3DR21-3DR1-3R1a.

MINOR AMENDMENT (68185)		2A	7-10-75	G.F.E.
KSA5 LEAD, MR4, LC5 & NOTE 4 ADDED.		2	14-2-74	G.F.E.
WIRE GAUGE WAS S.W.G. NEW COY. TCG. (122570)				
AMENDMENT PARTICULARS		ISSUE	DATE	APPO. REF.
NZPO		DRAWN	CHECKED	WIRING
		FP	RAB	REM
				CIRCUIT- REV. 35399 2/11/65

CORD CIRCUIT
50/1200 LINE P.A.B.X.
SIZE M 50 V W
15211
GBW

Centimeters

5
10
15
20
25

TO CORD CIRCUIT
LAMP & KEYS
GBW 15201
FIG. 2
OR EQUIV.

TO POSN. C.T.
GBW 15201
FIG. 1A
OR EQUIV.

TJ
2