



- NOTES:-**
- FUSING - 1.5A PER CIRCUIT
  - FOR ACTUAL CONNECTIONS SEE RELEVANT GRADING CHARTS.
  - BANK MULTIPLE CONNECTIONS TO THESE TERMINALS ARE SHOWN IN FIG. 1A
  - WHEN DIRECTLY CONNECTED TO CALL TRAP, ADD WIRING SHOWN THUS AND DELETE WIRING SHOWN THUS
  - Ø FOR WIRING SEE GBW 11770 OR EQUIV.
  - SHELF JACK POINTS U9 & U11 MAKE CONTACT WHEN SELECTOR IS REMOVED.
  - ALL WIRING TO BE 25 S.W.G. UNLESS OTHERWISE SPECIFIED.
  - P.G. ALARM BATT. IS REQD. ON INCOMING OR FIRST SELECTORS ONLY.

BATT. - BK. 22 S.W.G. FUSE (7B) U12  
 ETH. - R. 22 S.W.G. ETH. BAR (7A) U11  
 BATT. W. - U12-HDe-HBc-R4b-Ae-HA2-HCe-VMc-RMc-HA7  
 ETH. R. - U11-HB1-CDd-CD2-Ab-B1-B5-HA2a-HA9-S1-B6-R1a-TJ7-TJ9

TRUNK TANDEM SELECTOR			
200 OUTLET 4 WIRE			
2000 TYPE			
PG ALARM LAMP RE-INSTATED (744G7)	3	30763	D.B.H.
P2 & TT BANKS INTERCHANGED, PG ALM. DELT	2		
AMENDMENT PARTICULARS	ISSUE DATE	APPD.	REF.
NZPO			
DRAWN	CHECKED	WIRING	CIRCUIT
J.G.			L.A.J.
GBW 15980			