



- NOTES:**
- FUSING - 1.5 A PER CIRCUIT AND T.C.F.T. (GBW 16710).
  - SHELF JACK POINTS U9 & U11 TO MAKE CONTACT WHEN RELAY SET IS REMOVED.
  - U POINTS 12, 18, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30, 31 AND 32 ARE ALL WIRED TO THE SIMILARLY NUMBERED U POINTS OF THE ASSOCIATED CIRCUIT, GBW 16500, U POINTS TO BE WIRED TO U POINT 9 OF GBW 16500.
  - THE WINDINGS OF RELAY OC ARE CONNECTED DIFFERENTIALLY.
  - FOR WIRING SEE GBW 12110 OR EQUIV OR GBW 13730 OR EQUIV.
  - ALL WIRING NOT OTHERWISE SPECIFIED TO BE 25 S.W.G.
  - TO OBTAIN AN IMPULSE OUTPUT RATIO WITHIN THE SPECIFIED TEST LIMITS STRAP OUT RESISTORS R14-R16 INDIVIDUALLY OR IN PARALLEL COMBINATIONS AS REQUIRED AND ADJUST RV1.
  - ON EARLIER EQUIPMENT COLOUR OF BATTERY WIRING WAS BK OR W.
- NOTE 6**
- BATT. V. 22 S.W.G. FUSE 1B2 U12
- ETH. R. 22 S.W.G. ETH BAR 1A2 U11
- BATT. V. U12 - AAe - Be - BBb - BBc - CDe - TXa - De - RRe - TTe - TCFT - U13
- RCb - Rce - CFe - DBb - DBc - DDe - SFe - SRe - SAb - SAc
- RCe - RX4b
- RGe - DCe - Rbb - R5b - R6b - R2b
- ETH. R. U11 - AA2 - A2 - B21 - B23 - B5 - BB21 - CD21 - CD4 - D24 - RC2 - CF2 - CF5 - SR1 - SA1 - RG23 - RG4 - T1/E - SCA17 - R3b - TJ1

RETRACTED	(52317)	4A	2823/B-5H	PARENT EXCHANGE OIG LINE CIRCUIT FOR BOTHWAY JUNCTIONS FOR USE WITH I/C LINE CIRCUIT TO DEPENDENT EXCHANGE NZ. S.S.A.C. No 3 T
ALT. CONNECTIONS TO COINS 2 ADDED (18730)		4A	8470/RW	
CABLING TO U14 & U16 AMENDED (8737)		3	8128/BL	
RIS DELETED RV1, RV6 & NOTE 8 ADDED (8737)		2	7927/DJB	
	(8822)	1	2421/DJB	
AMENDMENT PARTICULARS	ISSUE DATE	APPD	REF. I.V.F.	SIZE L 50V 5
ZPO	DRAWN D.M.C.	CHECKED	WIRING CIRCUIT A.S.H.	GBW 16510