



FOR CONNECTIONS TO SUBS LINE EQUIP. SEE RELEVANT LINE CCT.

- NOTES:-
1. FUSE:- 1.5A PER CIRCUIT.
 2. ALL WIRING TO BE 25 SWG. UNLESS OTHERWISE SPECIFIED.
 3. SHELF JACK 'U' POINTS Ø & 11 TO MAKE CONTACT WHEN SELECTOR IS REMOVED.
 4. Ø FOR WIRING SEE GBW13730 OR EQUIV.
 5. LEVEL 1 CONTACT 11 TO BE MULTIPLIED & WIRED TO EARTH ON FINAL SELR. MULT. CONNECTION STRIP.
 6. RELAY 'OC' IS DIFFERENTIALLY CONNECTED.
 7. ON EARLY EQUIPMENT BATT. WIRE COLOUR WAS BK OR W.

BATT.V.:- U12-TDc-HR2-Hc-Ac-VME-RMc-R1b-R2b-R4b-RB1b-R6b
ETH.R.:- U11-HR1-D22-CD22+27-AB-A2-B1-B3-NR1-RE1-RB1d-TJ7

B WHEN TRUNK OFFER CALLS ORIGINATE FROM AN A.S.C. INSULATE CONTACTS HR25 & 26

NOTE 8 ADDED (63876)				4	198-81	J.R.	100 LINE FINAL SELECTOR ORDINARY U.A.X.N.Z.13.
MINOR MODS. (13265)				3.	3.3.70	R.W.	
MINOR MODIFICATION, NOTE 7 ADDED.				2.			
AMENDMENT PARTICULARS				ISSUE	DATE	APPR	REF
NZPO				DRAWN	CHECKED	WIRING	CIRCUIT
				WJC	24/7/64		
GBW 16660							

ETH BAR 3A2 U11
BATT FUSE V. 25WG U12 3B2

TJ A 01
A 02
A 010

3 NR TJ
3 4 14