

RELAY DESIGN FOR CIRCUIT GBW 12400

TITLE MANUAL BOARD OUTGOING CIRCUIT
FOR BOTHWAY 2.V.F. TOLL LINE FOR
EXCHANGES WITH SLEEVE DIALLING

COMMITTEE'S WIRING DIAGRAM N^o

RELAY NAME	COMM CODE	IF NEW CODE (CARD ATTACHED)	DEPARTURES FROM DIAGRAM		SPRING NUMBERING CONTACT UNIT NUMBER								REFERENCES TO NOTES BELOW		
			RESISTANCE	CONTACTS	1	2	3	4	5	6	7	8			
A	5796P				22 21	1 2									A1 B
B	6008				22 21	3 2									
D	5797				3 2										A2
DS	1671				1 2	22 21	5 4	24 23							
DT	2283				3 2	22 21									
IL	1061				1 2	24 23	5 4	22 21							
RA	2022						R E T A R D								
S	5798				1 2	22 21									
SR	4031				1 2	4 3	22 21								
TO	1053				3 2	22 21									

NOTES SPECIAL FACTORS OF SAFETY A
SPECIAL ADJUSTMENTS B
CIRCUIT POINTS OR MODIFICATIONS C

CLASS	RELAY	NOTES
A1 A2	A D	TEST & R.A. FIGURES OPERATE C.F.S. = 2.67

A	B	D	DS	DT	IL	RA	S	SR	TO	CCT. 2
A	B	D	DS	DT	IL	RA	S	SR	TO	CCT. 1

ORIGINATED BY **S.B.**
DATE
SIGNED FOR COMMITTEE *[Signature]*

CHANGES
ISSUE 1
15. 12. 53

0
5 Centimeters
10
15
20
25
30