



NOTES

- FOR EXTENSIONS BARRED DIRECT ACCESS TO MAIN EXCHANGE CUT STRAPS SHOWN — — & ADD STRAPS SHOWN — — —
- CUT STRAPS H C ON UNALLOTTED LINES
- FOR WIRING OF LEADS MARKED Ø SEE RELEVANT COMMON SERVICE DIAGRAM
- ALL WIRING TO BE 0.5mm UNLESS OTHERWISE SPECIFIED PLATE STRAPPING TO BE 0.6mm OR 0.5mm IF 0.5mm IS USED COLOURS IN BRACKETS TO BE DISREGARDED
- FUSE 1.5A PER 10 CCTS
- GBW NUMBERS SHOWN IN BRACKETS REFER TO EQUIPMENTS MANUFACTURED TO SPECIFICATIONS 05 1035 & 05 1058

TAGS ON MTS PLATE

BATT BK FUSE (10) 0.6mm 1L5b to 10R1b
1L5b to 10L5b
1C0b to 10C0b

ETH R ETH BAR (1A) 0.6mm 10L53 to 1L53
10C04 to 1C04
STRIP CONN E ETC

OUTLETS TO BE MULTIPLED & WIRED

EXTN NO	20 LINE PABX					35 & 49 LINE PABX				
	LF	CS	ES	EF	EF	LF	CS	ES	EF	EF
ATT 0	1	1	1	1	1	1	1	1	1	1
89	4	4	4	4	4	4	4	4	4	4
88	5	5	5	5	5	5	5	5	5	5
87	6	6	6	6	6	6	6	6	6	6
86	7	7	7	7	7	7	7	7	7	7
85	8	8	8	8	8	8	8	8	8	8
84	9	9	9	9	9	9	9	9	9	9
83	10	10	10	10	10	10	10	10	10	10
82	11	11	11	11	11	11	11	11	11	11
81	12	12	12	12	12	12	12	12	12	12
80	13	13	13	13	13	13	13	13	13	13
79	15	15	15	15	15	15	15	15	15	15
78	16	16	16	16	16	16	16	16	16	16
77	17	17	17	17	17	17	17	17	17	17
76	18	18	18	18	18	18	18	18	18	18
75	19	19	19	19	19	19	19	19	19	19
74	20	20	20	20	20	20	20	20	20	20
73	21	21	21	21	21	21	21	21	21	21
72	22	22	22	22	22	22	22	22	22	22
71	23	23	23	23	23	23	23	23	23	23
70	24	24	24	24	24	24	24	24	24	24
CALL WAITING PARKING POSN	-	-	-	25	-	-	-	-	-	25

NZ NOTES

A ON SOME 35 LINE SYSTEMS THE HF MULT WIRING IS BROWN INSTEAD OF WHITE

EXTENSION LINE CIRCUITS 20&35/49 LINE PABXS

REDRAWN & METRICATED (157608) 3B 6 9 78 FJM
N.Z. NOTE A ADDED (122098) SA 4 12 78

AMENDMENT PARTICULARS ISS DATE APP

SIZE A1 50V W

GBW 13210

NZPO DRAWN CHECKED WIRING CIRCUIT